

[2017-New-VersionBraindump2go 627q 400-201 Exam Dumps Free Download][141-150]

2017 May New: Cisco 400-201 Exam Dumps with VCE and PDF Free Updated in [www.Braindump2go.com](#) Today!100% Real Exam Questions! 100% Exam Pass Guaranteed! 1.|2017 Version New 400-201 Exam Dumps (PDF & VCE) 627Q&As Download: <http://www.braindump2go.com/400-201.html> 2.|2017 Version New 400-201 Exam Questions & Answers Download: <https://drive.google.com/drive/folders/0B75b5xYLjSSNbGVFRUFuUW5TR2c?usp=sharing> QUESTION 141What are three actions that the control word performs in MPLS AToM? (Choose three.) A. is used to identify the VC labelB. is used for padding small packetsC. preserves the sequence of the transported framesD. facilitates the load balancing of AToM packets in the MPLS backbone networkE. carries control bits of the Layer 3 header of the transported protocolF. is used to identify the tunnel label Answer: BCDEExplanation:<https://ccdewiki.wordpress.com/2013/05/28/control-word-on-atom/> QUESTION 142With EIGRP DUAL, a feasible successor is considered loop-free if which condition is true? A. Its AD is equal to the metric of the successorB. Its AD is less than the successor's FDC. Its AD is equal to the successor's FDD. Its AD is greater than the successor's FDE. Its FD is equal to the metric of the successor Answer: B QUESTION 143Customers connecting to a Service Provider for Internet access are intending to implement redundant peering. The design requirements call for preferring a primary link for both ingress and egress traffic. Secondary links should be used only during primary outages. What two BGP deployment options will accomplish this design goal? (Choose two.) A. On the router handling the secondary link, advertise routes with a MED value of 0.B. On the router handling the primary link, set the weight for all incoming routes to be a value of 0.C. On the router handling the secondary link, advertise all routes with a longer AS-PATH value.D. On the router handling the primary link, advertise all routes with a longer AS-PATH value.E. On the router handling the secondary link, set the local preference for all incoming routes to be a value of 0. Answer: CE QUESTION 144Refer to the exhibit. R1 and R2 are multicast routers running PIM over Serial1/0. The PIM adjacency on R1 is not forming with the given configuration. What command can be entered on R1 to resolve the issue? A. no access-list 100 deny 103 any anyB. no access-list 100 deny udp any any eq 103C. no access-list 100 deny ip any host 224.0.0.1D. no access-list 100 deny ip any host 224.0.0.2 Answer: AExplanation:All PIM protocols share a common control message format. PIM control messages are sent as raw IP datagrams (protocol number 103), either multicast to the link-local ALL PIM ROUTERS multicast group, or unicast to a specific destination. Reference: <http://www.metaswitch.com/resources/what-is-protocol-independent-multicast-pim> QUESTION 145There are two cabling schemes to choose from when implementing a Cisco CRS-1 multi shelf system: single module cabling and multi module cabling. What is the maximum capacity of the LCCs that are supported in multi module cabling? A. 9 LCCsB. 7 LCCsC. 10 LCCsD. 6 LCCsE. 8 LCCs Answer: A QUESTION 146Which statement about MPLS TE Fast Reroute (FRR) node protection operation is not correct? A. It requires a next-next hop backup tunnel.B. Point of local repair (PLR) swaps the next hop label and pushes the backup label. C. The backup tunnel terminates on the merge point (MP) where traffic rejoins the primary tunnel.D. The backup tunnel can have associated bandwidth capacity.E. Restoration time is expected under 50 ms. Answer: E QUESTION 147Regarding to EIGRP protocol, a "successor" is: A. A neighbor that has met the feasibility conditionB. A neighbor that has met the feasibility condition and has the lowest cost path towards the destinationC. Any neighbor that is in the path towards the destination.D. Any neighbor that is in the path towards the destination and whose reported distance equals the feasible distance. Answer: B QUESTION 148 Which three statements about MPLS Label Distribution Protocol (LDP) are valid? A. LDP hello packets are sent to UDP port 646 B. LDP hello packets are sent to TCP port 711C. LDP sessions are TCP sessions to port 646D. LDP sessions are TCP sessions to port 711E. LDP establishes a peer relationship with another router that must be directly attached.F. LDP can establishes a peer relationship with another router that is not directly attached Answer: ACF QUESTION 149Select two valid administratively scoped multicast addresses in networks running Interior Gateway protocols like EIGRP and OSPF (Choose two). A. 239.255.255.255B. 224.0.0.10C. 239.0.0.1D. 224.0.0.5 Answer: AC QUESTION 150A network engineer is designing the BGP aarchitecture with a requirement of preventing the AS from becoming a Transit AS path, using the following configuration:router bgp 65000neighbor 10.0.0.1 route-map BGP-ROUTE-POLICY inThe goal is to prevent routes learned from 10.0.0.1 from being advertised to any other eBGP peering in the AS 65000. What command should be used within the route map to achieve this goal while keeping existing route policies in place? A. set community no-export additiveB. set community no-advertiseC. set community no-advertise additiveD. set community no-export Answer: AExplanation:Setting no-advertise will block the route from being advertised to anywhere anywhere, question says it wants to prevent the AS from becoming transit, therefore no-export will stop any eBGP router advertising outbound and therefore stop transit. !!!RECOMMEND!!! 1.|2017 Version New 400-201 Exam Dumps (PDF & VCE) 627Q&As Download:<http://www.braindump2go.com/400-201.html> 2.|2017 Version New 400-201 Study Guide Video: YouTube

Video: [YouTube.com/watch?v=KrQHgsl_BtM](https://www.youtube.com/watch?v=KrQHgsl_BtM)